

# 24V TAP OUT™ HE STIK

Highly efficient 24V LED illumination for new & retrofit sign cabinet applications

24  
VDC

TAP OUT™  
STIK

## Specifications

- Dimensions L x W x H ..... See table x 0.72" x 0.30"
- Beam angle ..... 160° Low-dome batwing optic
- Color temperature (CCT) ..... 7000 K
- Efficacy ..... 140 lm/W
- Mounting options ..... Socket (retro) / Brackets (new)
- Operating temp. .... -40° C to +60° C
- Protection grade ..... IP67
- Power supply ..... Principal Sloan 24 VDC
- Wire color ..... Red (+) / Black (-)
- Packaging ..... Single-sided ..... 24 pieces per tube  
Double-sided ..... 16 pieces per tube
- Warranty ..... 10-year product/5-year limited labor



## Product Options



	Length	Nominal length	No. of mods	Lumens per Stik	Power	Max. units (96 W)	Whips	UL number*	SKU*
SINGLE-SIDED	18"	15.91"	3	555	3.96	24.00	1-3 ft.	PL-OP2-TO3-P/ST-SS-18-PW	B-TO-S03-01865-24-HE
	24"	21.91"	3	555	3.96	24.00		PL-OP2-TO3-P/ST-SS-24-PW	B-TO-S03-02465-24-HE
	30"	27.91"	4	740	5.28	18.00		PL-OP2-TO3-P/ST-SS-30-PW	B-TO-S04-03065-24-HE
	36"	33.91"	6	1110	7.92	12.00		PL-OP2-TO3-P/ST-SS-36-PW	B-TO-S06-03665-24-HE
	42"	39.91"	6	1110	7.92	12.00		PL-OP2-TO3-P/ST-SS-42-PW	B-TO-S06-04265-24-HE
	48"	45.91"	7	1295	9.24	10.00		PL-OP2-TO3-P/ST-SS-48-PW	B-TO-S07-04865-24-HE
	60"	57.91"	9	1665	11.88	8.00		PL-OP2-TO3-P/ST-SS-60-PW	B-TO-S09-06065-24-HE
	64"	61.91"	9	1665	11.88	8.00		PL-OP2-TO3-P/ST-SS-64-PW	B-TO-S09-06465-24-HE
	72"	69.91"	10	1850	13.2	7.00	1-6 ft.	PL-OP2-TO3-P/ST-SS-72-PW	B-TO-S10-07265-24-HE
	84"	81.91"	12	2220	15.84	6.00		PL-OP2-TO3-P/ST-SS-84-PW	B-TO-S12-08465-24-HE
	96"	93.91"	14	2590	18.48	5.00		PL-OP2-TO3-P/ST-SS-96-PW	B-TO-S14-09665-24-HE
	108"	105.91"	15	2775	19.8	4.00		PL-OP2-TO3-P/ST-SS-108-PW	B-TO-S15-10865-24-HE
	117"	114.91"	16	2960	21.12	4.00	PL-OP2-TO3-P/ST-SS-117-PW	B-TO-S16-11765-24-HE	
	120"	117.91"	17	3145	22.44	4.00	PL-OP2-TO3-P/ST-SS-120-PW	B-TO-S17-12065-24-HE	
DOUBLE-SIDED	18"	15.91"	6	1110	7.92	12.00	1-3 ft.	PL-OP2-TO3-P/ST-DS-18-PW	B-TO-D06-01865-24-HE
	24"	21.91"	6	1110	7.92	12.00		PL-OP2-TO3-P/ST-DS-24-PW	B-TO-D06-02465-24-HE
	30"	27.91"	8	1480	10.56	9.00		PL-OP2-TO3-P/ST-DS-30-PW	B-TO-D08-03065-24-HE
	36"	33.91"	12	2220	15.84	6.00		PL-OP2-TO3-P/ST-DS-36-PW	B-TO-D12-03665-24-HE
	42"	39.91"	12	2220	15.84	6.00		PL-OP2-TO3-P/ST-DS-42-PW	B-TO-D12-04265-24-HE
	48"	45.91"	14	2590	18.48	5.00		PL-OP2-TO3-P/ST-DS-48-PW	B-TO-D14-04865-24-HE
	60"	57.91"	18	3330	23.76	4.00		PL-OP2-TO3-P/ST-DS-60-PW	B-TO-D18-06065-24-HE
	64"	61.91"	18	3330	23.76	4.00		PL-OP2-TO3-P/ST-DS-64-PW	B-TO-D18-06465-24-HE
	72"	69.91"	20	3700	26.4	3.00	1-6 ft.	PL-OP2-TO3-P/ST-DS-72-PW	B-TO-D20-07265-24-HE
	84"	81.91"	24	4440	31.68	3.00		PL-OP2-TO3-P/ST-DS-84-PW	B-TO-D24-08465-24-HE
	96"	93.91"	28	5180	36.96	2.00		PL-OP2-TO3-P/ST-DS-96-PW	B-TO-D28-09665-24-HE
	108"	105.91"	30	5550	39.6	2.00		PL-OP2-TO3-P/ST-DS-108-PW	B-TO-D30-10865-24-HE
	117"	114.91"	32	5920	42.24	2.00	PL-OP2-TO3-P/ST-DS-117-PW	B-TO-D32-11765-24-HE	
	120"	117.91"	34	6290	44.88	2.00	PL-OP2-TO3-P/ST-DS-120-PW	B-TO-D34-12065-24-HE	

This product is covered by U.S. Patent No. 9,851,054.

Specifications subject to change without notice.



# 24V TAP OUT™ HE STIK

Highly efficient 24V LED illumination for new & retrofit sign cabinet applications

24  
VDC

TAP OUT STIK

## Recommended Coverage Chart (Cabinets)

Depth from stik to face	Estimated spacing between Stiks
7"	9"
8"+	12"
>12"	Use two banks single-sided

NOTE: Product and depth may vary depending on face material and desired brightness.



principalsloan.com

325.227.4577

3490 Venture Dr., San Angelo, TX 76905

© 2023 Principal Industries Rev A 2023-06-28

